Coldline
QUALITY COMMERCIAL ICE

Manual

| Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

Instructions For Ice Thickness Adjustment& How to Restore The Original

Parameters on the Control Panel

Firstly, please kindly note: "Ice Thickness +" (here after we say "+") is the first button to press if you wanna restore the original parameters; However, "Ice Thickness -" (here after we say "-") is the first button to press if you want to adjust the ice thickness.

Original Parameters Display   "+-" buttons

Ⅰ. Ice Thickness Adjustment

If you want to adjust the ice thickness, process this below operation after the water flows smoothly through the evaporator:

Press "-" firstly and hold on for around 3 seconds until the panel display new number such as "-01 " , then press"+" or   "-" to adjust the ice thickness.

Ⅱ. Restore The Original Parameters

Generally the original parameters is not allowed to be changed, but if customers change the numbers carelessly, please process the following steps to solve it:
1. Firstly check the display numbers as per our correct original numbers , for example model SK-500P: "220, 308 ,405, 501, 640, 708, 820, 901". If it is not same, we need to adjust the display numbers until it is same with the correct.

Here we take SK-500P as example. Adjustment operation: press"+" button, if the first number is 220, then press "+", come to display number 308, if it is not 308, now you need to press "-" to check whether it is 308, if it display the correct number 308, then we press "+" again" to come to 4-serial number, the next steps are same, just repeat it until all numbers are correct.

NOTE: Next time do not press"+" directly, because this may change the original parameters.